

BOYZE ROX36S

Spec Sheet

HIGH-POWER SUBWOOFER | DUAL 18"

ACOUSTICS

Max SPL	144 dB
Bandwidth (-10 dB)	25 Hz – 200 Hz
Directivity	Standard, End-Fire, or Cardioid (via BS20K-4 Presets)

TRANSDUCERS

LF Drivers	2 × 18" Neodymium Drivers
Voice Coil	5" Sandwich Voice Coil with Double Spider
Acoustical Load	Dual Independent Rear Volume / Independent Chambers

PHYSICAL

Weight	96.6 kg / 213 lbs
Depth	27"
Width	22"
Height	52.75"
Cabinet	Premium Birch Plywood
Connectors	1 × NL4 Connector
Rigging	Ground Stack; Standard Fly Rigging Available on Request

POWER HANDLING

NOMINAL IMPEDANCE: 4 Ω · BS20K-4 or BS17K-2			
CHANNEL	AES	PROGRAM	PEAK
LF (Full Power)	3,600 W	7,200 W	14,400 W

RECOMMENDED AMPLIFIERS

Primary	Boyce BS20K-4
Alternate	Boyce BS17K-2

DEPLOYMENT

Preset Configurations	Standard, End-Fire, and Cardioid
Standard	Horizontal or vertical ground stack
End-Fire	Extended LF throw via BS20K-4 Presets
Cardioid	Rear rejection via BS20K-4 Presets
Fly Rigging	Available on request